

Trade Name: Omnixon 2330

## **TECHNICAL DATA SHEET**

Date: 17-01-2020

# Omnixon 2330

**TDS Version: 1.0** 

Iron oxide pigment for colouration of concrete products, cement/lime mixtures and lime mortar products. According to DIN EN 12 878: 7/2014 CE – 1032 – CPR – 7883-01-14

#### **Product Properties**

- Inorganic, light-stable iron oxide pigment
- Allows efficient, even and reproducible coloration

#### Instructions on Use

- Manual dosing or with dosing equipment
- Ready to use

#### **Recommendable quantity**

- 2-6% of the weight of the binding agent
- Add directly to the gravel/sand mixture before cement and water is added
- Pre-mixing time: 10-30 seconds

#### **Technical features**

Form:	Powder	
Colour:	Black	
pH-value:	6,0 - 8,0	
Storage:	Protect against frost, strong sun and pollution.	
Durability:	In original packaging: unlimited.	
	Store in closed container.	
Supplied in:	Paper bags (25kg), Big Bags (1000kg)	

### **Declared properties**

	Category B	Category A
Setting time:	Min. initial time: 60min	Min. initial time: 60min
	Max. final time: 720 min	Max. final time: 720 min
Compressive strength:	= 8%</td <td><!--= 8%</td--></td>	= 8%</td
Pigment composition:	see Safety Data Sheet	see Safety Data Sheet
Water soluble substances:	= 0,5%</td <td><!--= 1,0%</td--></td>	= 1,0%</td
Chloride content:	= 0,1%</td <td><!--= 0,5%</td--></td>	= 0,5%</td
Total chlorine:	= 0,1%</td <td><!--= 0,5%</td--></td>	= 0,5%</td
Loss of ignition	= 2,0%</td <td><!--= 3,0%</td--></td>	= 3,0%</td
Hazardous content:	see Safety Data Sheet	see Safety Data Sheet

#### Safety instructions: see Safety Data Sheet

**Remarks:** These technical advices are recommendations according to present knowledge. The user is advised that it is essential to conduct prior tests to determine correct usage. **Assistance:** Please feel free to contact our technical laboratory.

This document contains data and information about the application and operation of our products. We cannot be held responsible for its correctness and completeness, either expressed or implied. This document may be changed without notice at any time. Statements, recommendations and the like, which are not included in this document, occur unauthorized and do not have a binding effect. The buyer bears the full risk related to application and use. From the moment of delivery of the products we do not have knowledge of or influence on the conditions and methods of storage, use and disposal or on the implementation of our recommendations. Thus, we cannot be held responsible from this moment on. As far as permitted by law, we are not liable for loss, destruction or damage from this point of time, provided that those result from handling, storage, use or disposal of the products or related. It is essential that the buyer makes own tests regarding the purchased products, technical assistance and information, in particular whether they are suitable for the intended use and application. These production-related test should include both the technical as well as the health, safety and environmental aspects of the desired product. Unless we agree otherwise in writing, the purchase and supply of products happens on the basis of our General Terms and conditions.