

**Datasheet for**

**Benoslip 2003**

**Description:**

Benoslip 2003 is a paraffin-based release agent.  
Benoslip 2003 is the ideal release agent, in which the highest technical demands for production of concrete goods, concrete pipes etc.  
Benoslip 2003 is a cold resistant chemical release agent, which do not cause discolouration of concrete

**Operation:**

Benoslip 2003 can be used as a release agent for precast, concrete goods as well as casting on a construction site (wet casting).  
Can be applied on all surfaces such as steel/metal, wood, plastic.  
It can be universally used and is especially well-suited, where the demands for concrete surfaces are high, for maintenance of moulding equipment as well as protective oils for concrete trucks

**Advantage:**

Benoslip 2003 gives no discolouration of concrete surfaces  
Benoslip 2003 leaves a clean surface.  
Benoslip 2003 gives least possible amount of pores in the concrete surface

**Dosage:**

Benoslip 2003 should be applied with spraying equipment. The best result is achieved by applying a thin uniform layer. Potential surplus Benoslip 2003 is removed with a cloth.  
Remember over-dosage causes a reduction of demoulding ability. Range is 40 m<sup>2</sup> pr. ltr., though dependable on the moulds suction and method of appliance.

**Limitation:**

Must not be mixed with additional products

**Physical properties:**

Appearance :	Clear liquid
Odour :	weak
pH :	Not relevant
Boiling point:	-
Flash point :	>100°C
Density :	0,845 g/ml
Water dissol.:	non-water dissolvable
MAL-code :	00-1

**Contains:**

Paraffin oils :	> 80%
Alkanes :	< 20%

